

Model	CFM FREE AIR @ INCHES H2O				MAX DUTY	HP	PHASE	NO. FILTERS	RUNNING WATTS @ INCHES WATER	MAX STARTING WATTS	VOLTAGE	FLA	HEIGHT W/O FILTER	HEIGHT W/O INLET	OUTLET HOSE PIPE SIZE	WEIGHT	PRICE Tax & Shipping extra
	20"	30"	40"	50"													
APS11A	13				34"	1/8HP	1	1	198W/20"	900W	110/220	2.0A/110V	10"	8"	1"	23 lbs	\$1,056.80 CAD
APS21	27	19	7		43"	1/3HP	1	1	377W/30"	1,800W	110/220	3.8A/110V	10"	9"	1"	28 lbs	\$1,178.38 CAD
APS31	34	28	21	16	56"	1/2HP	1	1	471W/30"	2,000W	110/220	5.6A/110V	10"	10"	1.5"	36 lbs	\$1,251.62 CAD
APS313	34	28	21	16	56"	1/2HP	3	1	410W/30"	4,000W	220/440	2.0A/220V	10"	10"	1.5"	36 lbs	\$1,291.80 CAD
APS41	70	65	53	36	58"	1 HP	1	1	971W/40"	4,000W	110/220	9.8A/110V	12"	12"	1.5"	50 lbs	\$1,524.12 CAD
APS43	70	65	53	36	58"	1 HP	3	1	850W/40"	5,000W	220/440	3.2A/220V	12"	12"	1.5"	50 lbs	\$1,528.74 CAD
APS45	110	100	90	80	65	1.5HP	1	2	1,430W/4W	9,000W	110/220	10.4A/220V	14"	15	2"	77lb	\$2,043.72 CAD
APS453AQ	110	100	90	80	65	1.5HP	3	2	1,500W/4W	12,000W	220/440	4.9A/220V	14"	15	2"	85 lbs	\$2,084.60 CAD

**Includes:**

**Inlet Kits** include air filter, PVC elbow, bushing nipple and pipe.  
**Outlet Kits** include PVC nipple, stainless steel clamps and 6" outlet hose.  
**Cords** are 8', 3-prong, 14/3 gauge in 115V or 230V. Specify Voltage at order.

**Automatic Thermal Overload Protection\***

Should a power brownout occur and trip the motor, the Sweetwater® blower will automatically restart after cooling

**Air Filter**

Low-restriction inlet, washable filter that removes particulates to 50 microns included in price.



**Antiseize Compound**

Sweetwater® is assembled with antiseize compound to ensure easy disassembly when it becomes necessary years down the road.

**High-Efficiency Premium Motor**

Runs cool, is completely enclosed and fan cooled for the utmost reliability in humid environments. Universal 50/60 Hz, UL-, CSA- and CE-compliant.

**Flexible outlet hose**

simplifies installation.